



Passenger car engine oils - Mineral

Eurol Supreme Classic 10W-40

ZDDP Fortified premium mineral engine oil for classic cars

Description

Eurol Supreme Classic 10W-40 is an engine oil for older and restored engines from 1950 till 1994. This oil offers improved wear protection, in particular for plain bearings used in older engines.

By using carefully selected quality base oils and high levels of traditional anti-wear additives (ZDDP), this oil extends service life of older engines (by reducing cam wear).

Eurol Supreme Classic 10W-40 offers a very good oxidation stability to avoid sludge formation at high temperatures. Deposits are prevented by an effective cleaning action.

This oil is compatible with all seal materials and suitable for engines with and without turbochargers. It provides an easy start and can be used as a year round oil for temperatures above -25 °C.

Eurol Supreme Classic 10W-40 is applicable for use in American, European and Asian engines requiring ACEA A3/B4 or API SL/SJ (or older) where a SAE grade 10W-30, 10W-40 or 15W-40 was originally recommended.

Recommended for use

- API SJ/SL
- ACEA A3/B4
- MB 229.1

Physical properties

Colour	brown	
Density at 20°C	0.861 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	100.9 cSt	ASTM D 445
Viscosity, kinematic at 100°C	15.1 cSt	ASTM D 445
Viscosity Index	157	ASTM D 2270
Viscosity, dynamic (CCS)	4904 cP	ASTM D 5293
Base number	10.1 mg	ASTM D 2896
Sulphated ash	1.5 wt%	ASTM D 874
Zinc	0.14 wt%	
Phosphorus	0.12 wt%	
Flash point	220 °C	ASTM D 93
Pour point	-36 °C	ASTM D 97

Article number E100256
Version 5.0, 10-09-2021

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.