

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Date of issue: 11-2-2014 Revision date: 31-5-2016 Supersedes: 26-2-2015 Version: 1.2

1.1. Product identifier	
Product form	: Mixture
Product name	: Eurol Super Lite 5W-40
Product code	: E100092
Product group	: Trade product
1.2. Relevant identified uses of the	e substance or mixture and uses advised against
1.2.1. Relevant identified uses	
Intended for general public	
Main use category	: industrial use, professional use, consumer use
Use of the substance/mixture	: Lubricant
Function or use category	: Lubricants and additives
1.2.2. Uses advised against No additional information available	
1.3. Details of the supplier of the s	safety data sheet
Eurol bv. Energiestraat 12 P.O. Box P.O. Box 135 7442 DA Nijverdal - The Netherlands T +31 548 615165 r.hilgers@eurol.com - www.eurol.com	
1.4. Emergency telephone number	r
Emergency number	: +31 548 615165
SECTION 2: Hazards identificat 2.1. Classification of the substance	
Classification according to Regulation	(FO) No. 4070/0000 [O] DI
	(EC) NO. 12/2/2008 [CLP]
	(EC) NO. 12/2/2008 [CLP]
Not classified Adverse physicochemical, human heal	
Not classified Adverse physicochemical, human heal No additional information available	
Not classified Adverse physicochemical, human heal No additional information available 2.2. Label elements	th and environmental effects
Not classified Adverse physicochemical, human heal No additional information available 2.2. Label elements Labelling according to Regulation (EC)	th and environmental effects
Not classified Adverse physicochemical, human heal No additional information available 2.2. Label elements Labelling according to Regulation (EC) Precautionary statements (CLP)	th and environmental effects No. 1272/2008 [CLP] P102 - Keep out of reach of children. EUH208 - Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs,
Not classified Adverse physicochemical, human heal No additional information available 2.2. Label elements Labelling according to Regulation (EC) Precautionary statements (CLP) EUH-statements	th and environmental effects No. 1272/2008 [CLP] : P102 - Keep out of reach of children. : EUH208 - Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs, calcium salts, Benzenesulfonic acid,methyl-mono-20-26-branched alkylderivates, calcium sal
Not classified Adverse physicochemical, human heal No additional information available	th and environmental effects No. 1272/2008 [CLP] : P102 - Keep out of reach of children. : EUH208 - Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs, calcium salts, Benzenesulfonic acid,methyl-mono-20-26-branched alkylderivates, calcium sal May produce an allergic reaction.
Not classified Adverse physicochemical, human heal No additional information available 2.2. Label elements Labelling according to Regulation (EC) Precautionary statements (CLP) EUH-statements Child-resistant fastening Tactile warning	 th and environmental effects No. 1272/2008 [CLP] P102 - Keep out of reach of children. EUH208 - Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs, calcium salts, Benzenesulfonic acid,methyl-mono-20-26-branched alkylderivates, calcium sal May produce an allergic reaction. Not applicable
Not classified Adverse physicochemical, human heal No additional information available 2.2. Label elements Labelling according to Regulation (EC) Precautionary statements (CLP) EUH-statements Child-resistant fastening	 th and environmental effects No. 1272/2008 [CLP] P102 - Keep out of reach of children. EUH208 - Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs, calcium salts, Benzenesulfonic acid,methyl-mono-20-26-branched alkylderivates, calcium sal May produce an allergic reaction. Not applicable

SECT	SECTION 3: Composition/information on ingredients		
3.1.	Substances		
Not ap	plicable		
27-2-20	18 EN (English)	1/8	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic	(CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index-No.) 649-467-00-8 (REACH-no) 01-2119484627-25	>= 50	Asp. Tox. 1, H304
Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil- based	(CAS-No.) 72623-87-1 (EC-No.) 276-738-4 (REACH-no) 01-2119474889-13	10 - 25	Asp. Tox. 1, H304
Highly refined mineral oil (C15 -C50) substance with a Community workplace exposure limit		3 - 5	Not classified
Amines, polyethylenepoly-,reaction products with 1,3-dioxolan- 2-2one and succinic anhydride monopolyisobutenyl derivs	(CAS-No.) 147880-09-9 (EC-No.) 604-611-9	1 - 3	Aquatic Chronic 4, H413
Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts	(CAS-No.) 722503-68-6	1 - 3	Skin Sens. 1B, H317 Aquatic Chronic 4, H413
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3- dimethylbutyl) esters, zinc salts	(CAS-No.) 68784-31-6 (EC-No.) 272-238-5 (REACH-no) 01-2119657973-23	1 - 3	Eye Dam. 1, H318 Aquatic Chronic 2, H411
Phenol, dodecyl-, sulfurized, cabonates, calcium salt, overbased	(CAS-No.) 68784-26-9 (EC-No.) 272-234-3 (REACH-no) 01-2119524004-56	1 - 3	Aquatic Chronic 4, H413
Reaction products of Benzeneaminephenyl- with nonene (branched) phenyl- with nonene (branched)	(CAS-No.) 36878-20-3 (EC-No.) 253-249-4 (REACH-no) 01-2119488911-28	1 - 3	Aquatic Chronic 4, H413

Full text of H-statements: see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measur	es
First-aid measures general	: Seek medical attention if ill effect develops.
First-aid measures after inhalation	: Take victim to fresh air, in a quiet place, in an half laying position and if necessary take medica advice. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. High-pressure injection under skin may cause serious damage. Seek medical attention if ill effect or irritation develops.
First-aid measures after eye contact	 Remove contact lenses, if present and easy to do. Continue rinsing. Ensure adequate flushing of eyes by separating eyelids with the fingers. Obtain medical attention if pain, blinking, tears or redness persist.
First-aid measures after ingestion	: Consult a doctor/medical service if you feel unwell. If vomiting occurs spontaneously, keep head below the hips to prevent aspiration. Do not induce vomiting.
4.2. Most important symptoms and	d effects, both acute and delayed
Symptoms/effects after inhalation	At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.
Symptoms/effects after skin contact	: Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis. High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.
Symptoms/effects after eye contact	: Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.
Symptoms/effects after ingestion	 Bad taste. Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhoea.
Symptoms/effects upon intravenous administration	: Unknown.
4.3. Indication of any immediate m	edical attention and special treatment needed
Treat symptomatically.	
SECTION 5: Firefighting measured	res
5.1. Extinguishing media	
Suitable extinguishing media	: Carbon dioxide (CO2), dry chemical powder, foam. Water fog.
Unsuitable extinguishing media	: Do not use a heavy water stream. Use of heavy stream of water may spread fire.
5.2. Special hazards arising from t	he substance or mixture
Fire hazard	: Combustion generates: CO, CO2, POx, NOx, SOx, H2S. Metallic oxides.

: Not expected to be a fire/explosion hazard under normal conditions of use.

Explosion hazard

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

5.3. Advice for firefighters	
Precautionary measures fire Firefighting instructions Protection during firefighting Other information	 Do not enter fire area without proper protective equipment, including respiratory protection. Use water spray or fog for cooling exposed containers. Use self-contained breathing apparatus and chemically protective clothing. Prevent fire fighting water from entering the environment. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations.
SECTION 6: Accidental release mea	asures
6.1. Personal precautions, protective e	quipment and emergency procedures
General measures	: Spill area may be slippery. Prevent soil and water pollution. Prevent entry to sewers and public waters.
6.1.1. For non-emergency personnel	
Protective equipment	When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required. Use protective clothing.
Emergency procedures	: Consider evacuation.
6.1.2. For emergency responders	
Protective equipment	: When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.
Emergency procedures	: No specific measures are necessary.
6.2. Environmental precautions	

Dike for recovery or absorb with appropriate material. Notify authorities if product enters sewers or public waters. Prevent soil and water pollution. Prevent liquid from entering sewers, watercourses, underground or low areas. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

6.3.	Methods and material for containment and cleaning up		
For cont	ainment	:	Large quantities: Contain large spillage with sand or earth.
Methods	for cleaning up	:	Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Take up large spills with pump or vacuum and finish with dry chemical absorbent.
Other in	formation	:	Use suitable disposal containers. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations. On water, recover/skim from surface and pour out in disposal container.
6.4.	Reference to other sections		

For further information refer to section 13.

SECTION 7: Handling and stora	ge
7.1. Precautions for safe handling	
Additional hazards when processed	: Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. In not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.
Precautions for safe handling	: Avoid prolonged and repeated contact with skin. May be dangerously slippery if spilled. Whe contact with eyes or skin is likely, wear suitable protection. Do not eat, drink or smoke during use. Remove contaminated clothing and shoes.
Hygiene measures	Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems. Handle in accordance with good industrial hygiene and safety practice. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Where contact wit eyes or skin is likely, wear suitable protection. Wash contaminated clothing before reuse.
7.2. Conditions for safe storage, in	cluding any incompatibilities
Technical measures	: Keep container tightly closed and in well ventilated place.
Storage conditions	: Store in original container.
Incompatible products	: Reacts vigorously with strong oxidizers and acids.
Maximum storage period	: 5 year
Storage temperature	: ≤ 40 °C
Information on mixed storage	: Keep away from : oxidizing materials. strong acids.
Storage area	: Store at ambient temperature.
Special rules on packaging	: Keep container tightly closed and dry.
7.3. Specific end use(s)	
No additional information available	
27.2.2018	EN (English)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 8: Exposure controls/personal protection				
8.1. Control parameters				
Highly refined mineral oil (C15 -C50)				
EU IOELV TWA (mg/m ³) 5 mg/m ³				
		-		

Exposure-value for oil mist

: 10 mg/m3 (15 min.) or 5 mg/m3 (8 hours).

8.2. Exposure controls

Appropriate engineering controls:

Large quantities: Contain large spillage with sand or earth.

Personal protective equipment:

Gloves. In case of splash hazard: safety glasses. Eye protection should only be necessary where liquid could be splashed or sprayed.

Materials for protective clothing:

PVC gloves. Neoprene or nitrile rubber gloves

Hand protection:

In case of repeated or prolonged contact wear gloves. The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream). The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

Eye protection:

Eye protection should only be necessary where liquid could be splashed or sprayed

Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use. Avoid repeated or prolonged skin contact. If repeated skin contact or contamination of clothing is likely, protective clothing should be worn. Equipment should conform to EN 166.

Respiratory protection:

Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. Respiratory protective equipment must be checked to ensure it fits correctly each time it is worn. Provided an air-filtering/air-purifying respirator is suitable, a filter for particulates can be used for mist or fume. Use filter type P or comparable standard. A combination filter for particles and organic gases and vapours (boiling point >65°C) may be required if vapour or abnormal odour is also present due to high product temperature. Use filter type AP or comparable standard.

Personal protective equipment symbol(s):



Environmental exposure controls:

See Heading 12. See Heading 6.

Consumer exposure controls:

PVC gloves. Neoprene or nitrile rubber gloves.

Other information:

Do not put the product-soaked rags into the pockets of working clothes. Do not use cloths stained with the product to dry hands. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke during use. Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties		
9.1. Information on basic physical and	d chemical properties	
Physical state	: liquid	
Appearance	: Oily. liquid.	
Colour	: Brown.	
Odour	: characteristic.	
Odour threshold	: no data available	
pH	: no data available	
Relative evaporation rate (butylacetate=1)	: < 0,1	
Melting point	: no data available	
Freezing point	: no data available	
07.0.0010		4/0

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Boiling point	: > 280 °C
Flash point	: 202 °C
Auto-ignition temperature	: > 240 °C
Decomposition temperature	: no data available
Flammability (solid, gas)	: no data available
Vapour Pressure 20°C	: < 0,1 hPa
Relative vapour density at 20 °C	: >1 (air=1)
Relative density	: no data available
Density	: 0,85 - 0,86 kg/l
Solubility	: insoluble in water.
Log Pow	: >3
Viscosity, kinematic	: 200 - 300 cSt
Viscosity, dynamic	: no data available
Explosive properties	: no data available
Oxidising properties	: no data available
Explosive limits	: 0,6 - 7 vol %
9.2. Other information	
VOC content	: 0%
Other properties	: Gas/vapour heavier than air at 20'C.

SECTIO	N 10: Stability and reactivity	
10.1. F	Reactivity	
Stable under normal conditions of use.		
10.2.	Chemical stability	
Stable und	ler normal conditions.	
10.3. I	Possibility of hazardous reactions	
Refer to se	action 10.1 on Reactivity.	
10.4.	Conditions to avoid	
Moisture.	Overheating.	
10.5. I	ncompatible materials	
Strong oxid	dizing agents. strong acids.	
10.6. I	Hazardous decomposition products	
~~ ~~~		

CO, CO2, POx, NOx, SOx, H2S. Metallic oxides.

SECTION 11: Toxicological information			
11.1. Information on toxicological effects			
Acute toxicity (oral)	: Not classified		
Acute toxicity (dermal)	: Not classified		
Acute toxicity (inhalation)	: Not classified		
Reaction products of Benzeneaminephenyl-	vith nonene (branched) phenyl- with nonene (branched) (36878-20-3)		
LD50 oral rat	> 5000 mg/kg (OECD 401 method)		
LD50 dermal rat	> 2000 ml/kg (OECD 402 method)		
Distillates (petroleum), hydrotreated heavy pa	Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
LD50 oral rat	> 5000 mg/kg		
LD50 dermal rat	> 5000 mg/kg		
LC50 inhalation rat (mg/l)	> 5,53 mg/l		
Skin corrosion/irritation	: Not classified		
Serious eye damage/irritation	: Not classified		
Respiratory or skin sensitisation	: Not classified		
Germ cell mutagenicity	: Not classified		
Carcinogenicity	: Not classified		
Reproductive toxicity	: Not classified		

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Eurol Super Lite 5W-40	
Viscosity, kinematic	200 - 300 mm²/s
Other information	: Toxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the toxicology of similar products. Likely route of

based on a knowledge of the components and the toxicology of similar products. Likely route of exposure: ingestion, skin and eye.

	on				
12.1. Toxicity					
Ecology - general	: Ecotoxicological data have not been determined specifically for this product. Information giver is based on a knowledge of the components and the ecotoxicology of similar products.				
Ecology - water	This product floats on water and may affect the oxygen-balance in the water.				
Acute aquatic toxicity	xicity : Not classified				
Chronic aquatic toxicity	: Not classified				
Phenol, dodecyl-, sulfurized, cabonates, o	alcium salt, overbased (68784-26-9)				
LC50 other aquatic organisms 2	0 other aquatic organisms 2 > 100 mg/l 96h, Crangon crangon				
EC50 Daphnia 1	> 1000 mg/l EC50 48h - Daphnia magna [mg/l]				
ErC50 (algae)	> 500 mg/l 96h, Pseudokirchneriella subcapitata				
NOEC chronic fish	> 1000 mg/l 96h, Pimephales promelas (OECD 2013				
Reaction products of Benzeneaminephen	yl- with nonene (branched) phenyl- with nonene (branched) (36878-20-3)				
LC50 fish 1	> 100 mg/l 96h; Brachydanio rerio (zebra-fish)				
EC50 Daphnia 1	> 100 mg/l EC50 48h - Daphnia magna [mg/l]				
EC50 72h algae (1)	600 mg/l				
ErC50 (algae)	> 100 mg/l 72h; Desmodesmus subspicauts				
Distillates (petroleum), hydrotreated heav	y paraffinic (64742-54-7)				
LC50 fish 1	100 mg/l				
EC50 Daphnia 1	10000 mg/l				
12.2 Develotorics and degradability					
12.2. Persistence and degradability					
Eurol Super Lite EW 40					
Eurol Super Lite 5W-40					
Persistence and degradability	Not readily biodegradable.				
Persistence and degradability Phenol, dodecyl-, sulfurized, cabonates, o	calcium salt, overbased (68784-26-9)				
Persistence and degradability Phenol, dodecyl-, sulfurized, cabonates, c BOD (% of ThOD)	alcium salt, overbased (68784-26-9) 13,4 % ThOD				
Persistence and degradability Phenol, dodecyl-, sulfurized, cabonates, c BOD (% of ThOD) Reaction products of Benzeneaminephen	alcium salt, overbased (68784-26-9) 13,4 % ThOD yl- with nonene (branched) phenyl- with nonene (branched) (36878-20-3)				
Persistence and degradability Phenol, dodecyl-, sulfurized, cabonates, of BOD (% of ThOD) Reaction products of Benzeneaminephen Biodegradation	calcium salt, overbased (68784-26-9) 13,4 % ThOD yl- with nonene (branched) phenyl- with nonene (branched) (36878-20-3) 0 % Sturm - 28 days				
Persistence and degradability Phenol, dodecyl-, sulfurized, cabonates, c BOD (% of ThOD) Reaction products of Benzeneaminephen	calcium salt, overbased (68784-26-9) 13,4 % ThOD yl- with nonene (branched) phenyl- with nonene (branched) (36878-20-3) 0 % Sturm - 28 days				
Persistence and degradability Phenol, dodecyl-, sulfurized, cabonates, of BOD (% of ThOD) Reaction products of Benzeneaminephen Biodegradation	calcium salt, overbased (68784-26-9) 13,4 % ThOD yl- with nonene (branched) phenyl- with nonene (branched) (36878-20-3) 0 % Sturm - 28 days				
Persistence and degradability Phenol, dodecyl-, sulfurized, cabonates, of BOD (% of ThOD) Reaction products of Benzeneaminephen Biodegradation Distillates (petroleum), hydrotreated heav Biodegradation	calcium salt, overbased (68784-26-9) 13,4 % ThOD yl- with nonene (branched) phenyl- with nonene (branched) (36878-20-3) 0 % Sturm - 28 days y paraffinic (64742-54-7)				
Persistence and degradability Phenol, dodecyl-, sulfurized, cabonates, of BOD (% of ThOD) Reaction products of Benzeneaminephen Biodegradation Distillates (petroleum), hydrotreated heav Biodegradation	calcium salt, overbased (68784-26-9) 13,4 % ThOD yl- with nonene (branched) phenyl- with nonene (branched) (36878-20-3) 0 % Sturm - 28 days y paraffinic (64742-54-7)				
Persistence and degradability Phenol, dodecyl-, sulfurized, cabonates, o BOD (% of ThOD) Reaction products of Benzeneaminephen Biodegradation Distillates (petroleum), hydrotreated heav Biodegradation 2.3. Bioaccumulative potential	calcium salt, overbased (68784-26-9) 13,4 % ThOD yl- with nonene (branched) phenyl- with nonene (branched) (36878-20-3) 0 % Sturm - 28 days y paraffinic (64742-54-7)				
Persistence and degradability Phenol, dodecyl-, sulfurized, cabonates, of BOD (% of ThOD) Reaction products of Benzeneaminephen Biodegradation Distillates (petroleum), hydrotreated heav Biodegradation 2.3. Bioaccumulative potential Eurol Super Lite 5W-40	calcium salt, overbased (68784-26-9) 13,4 % ThOD yl- with nonene (branched) phenyl- with nonene (branched) (36878-20-3) 0 % Sturm - 28 days y paraffinic (64742-54-7) 31 %				
Persistence and degradability Phenol, dodecyl-, sulfurized, cabonates, c BOD (% of ThOD) Reaction products of Benzeneaminephen Biodegradation Distillates (petroleum), hydrotreated heav Biodegradation 2.3. Bioaccumulative potential Eurol Super Lite 5W-40 Log Pow	salcium salt, overbased (68784-26-9) 13,4 % ThOD yl- with nonene (branched) phenyl- with nonene (branched) (36878-20-3) 0 % Sturm - 28 days y paraffinic (64742-54-7) 31 % > 3 This product is not expected to bioaccumulate through food chains in the environment.				
Persistence and degradability Phenol, dodecyl-, sulfurized, cabonates, o BOD (% of ThOD) Reaction products of Benzeneaminephen Biodegradation Distillates (petroleum), hydrotreated heav Biodegradation 12.3. Bioaccumulative potential Eurol Super Lite 5W-40 Log Pow Bioaccumulative potential	salcium salt, overbased (68784-26-9) 13,4 % ThOD yl- with nonene (branched) phenyl- with nonene (branched) (36878-20-3) 0 % Sturm - 28 days y paraffinic (64742-54-7) 31 % > 3 This product is not expected to bioaccumulate through food chains in the environment.				
Persistence and degradability Phenol, dodecyl-, sulfurized, cabonates, of BOD (% of ThOD) Reaction products of Benzeneaminephen Biodegradation Distillates (petroleum), hydrotreated heav Biodegradation 12.3. Bioaccumulative potential Eurol Super Lite 5W-40 Log Pow Bioaccumulative potential Phenol, dodecyl-, sulfurized, cabonates, of	salcium salt, overbased (68784-26-9) 13,4 % ThOD yl- with nonene (branched) phenyl- with nonene (branched) (36878-20-3) 0 % Sturm - 28 days y paraffinic (64742-54-7) 31 % > 3 This product is not expected to bioaccumulate through food chains in the environment. salcium salt, overbased (68784-26-9)				
Persistence and degradability Phenol, dodecyl-, sulfurized, cabonates, of BOD (% of ThOD) Reaction products of Benzeneaminephen Biodegradation Distillates (petroleum), hydrotreated heav Biodegradation 12.3. Bioaccumulative potential Eurol Super Lite 5W-40 Log Pow Bioaccumulative potential Phenol, dodecyl-, sulfurized, cabonates, of Bioconcentration factor (BCF REACH) Log Pow	salcium salt, overbased (68784-26-9) 13,4 % ThOD yl- with nonene (branched) phenyl- with nonene (branched) (36878-20-3) 0 % Sturm - 28 days y paraffinic (64742-54-7) 31 % > 3 This product is not expected to bioaccumulate through food chains in the environment. salcium salt, overbased (68784-26-9) 2,2				
Persistence and degradability Phenol, dodecyl-, sulfurized, cabonates, of BOD (% of ThOD) Reaction products of Benzeneaminephen Biodegradation Distillates (petroleum), hydrotreated heav Biodegradation 2.3. Bioaccumulative potential Eurol Super Lite 5W-40 Log Pow Bioaccumulative potential Phenol, dodecyl-, sulfurized, cabonates, of Bioconcentration factor (BCF REACH) Log Pow	salcium salt, overbased (68784-26-9) 13,4 % ThOD yl- with nonene (branched) phenyl- with nonene (branched) (36878-20-3) 0 % Sturm - 28 days y paraffinic (64742-54-7) 31 % > 3 This product is not expected to bioaccumulate through food chains in the environment. salcium salt, overbased (68784-26-9) 2,2 9,5				
Persistence and degradability Phenol, dodecyl-, sulfurized, cabonates, of BOD (% of ThOD) Reaction products of Benzeneaminephen Biodegradation Distillates (petroleum), hydrotreated heav Biodegradation 2.3. Bioaccumulative potential Eurol Super Lite 5W-40 Log Pow Bioaccumulative potential Phenol, dodecyl-, sulfurized, cabonates, of Bioconcentration factor (BCF REACH) Log Pow Reaction products of Benzeneaminephen Bioconcentration factor (BCF REACH)	salcium salt, overbased (68784-26-9) 13,4 % ThOD yl- with nonene (branched) phenyl- with nonene (branched) (36878-20-3) 0 % Sturm - 28 days y paraffinic (64742-54-7) 31 % > 3 This product is not expected to bioaccumulate through food chains in the environment. salcium salt, overbased (68784-26-9) 2,2 9,5 yl- with nonene (branched) phenyl- with nonene (branched) (36878-20-3)				
Persistence and degradability Phenol, dodecyl-, sulfurized, cabonates, of BOD (% of ThOD) Reaction products of Benzeneaminephen Biodegradation Distillates (petroleum), hydrotreated heav Biodegradation 12.3. Bioaccumulative potential Eurol Super Lite 5W-40 Log Pow Bioaccumulative potential Phenol, dodecyl-, sulfurized, cabonates, of Bioconcentration factor (BCF REACH) Log Pow Reaction products of Benzeneaminephen Bioconcentration factor (BCF REACH)	salcium salt, overbased (68784-26-9) 13,4 % ThOD yl- with nonene (branched) phenyl- with nonene (branched) (36878-20-3) 0 % Sturm - 28 days y paraffinic (64742-54-7) 31 % > 3 This product is not expected to bioaccumulate through food chains in the environment. salcium salt, overbased (68784-26-9) 2,2 9,5 yl- with nonene (branched) phenyl- with nonene (branched) (36878-20-3)				

No additional information available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.6. Other adverse effects					
No additional information available					
SECTION 13: Disposal considera	tions				
13.1. Waste treatment methods					
Regional legislation (waste)	: Disposal must be done according to official regulations.				
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Do not discharge into drains or the environment.				
Additional information	: Hazardous waste.				
Ecology - waste materials	: Every mixture with foreign substances such as solvents, brake- and cooling liquids is forbidden. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. When not empty dispose of this container at hazardous or special waste collection point.				
European List of Waste (LoW) code	: 13 02 06* - Synthetic engine, gear and lubricating oils				

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID		
14.1. UN number						
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable		
14.2. UN proper shipping name						
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable		
14.3. Transport hazard class(es)						
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable		
14.4. Packing group						
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable		
14.5. Environmental hazards						
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No		
No supplementary information available						

14.6. Special precautions for user

- Overland transport

no data available

- Transport by sea no data available

- Air transport

no data available

- Inland waterway transport

no data available

- Rail transport

no data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions Contains no substance on the REACH candidate list Contains no REACH Annex XIV substances

VOC content : 0 %

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2		
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4		
Asp. Tox. 1	Aspiration hazard, Category 1		
Eye Dam. 1	Serious eye damage/eye irritation, Category 1		
Skin Sens. 1B	Skin sensitisation, category 1B		
H304	May be fatal if swallowed and enters airways.		
H317	May cause an allergic skin reaction.		
H318	Causes serious eye damage.		
H411	Toxic to aquatic life with long lasting effects.		
H413	May cause long lasting harmful effects to aquatic life.		
EUH208	Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs, calcium salts, Benzenesulfonic acid, methyl-mono-20-26-branched alkylderivates, calcium salts. May produce an allergic reaction.		

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product