





Transmission oils - Mineral

Eurol HPG EP SAE 85W-90 GL5

Mineral gear oil for hypoid gears and hub reductions

Description

Eurol HPG 85W-90 is a mineral gear oil, formulated according to the latest phosphor - sulphur technology. This special additive technology assures an excellent protection against metal-to-metal contact of the gears under the most severe operating conditions, even under shock loads.

Eurol HPG 85W-90 contains special additives, leaving a protecting oil film for optimum corrosion protection.

Eurol HPG 85W-90 shows an excellent oxidation and thermal stability. Seals are not affected by this product.

Eurol HPG 85W-90 is recommended for use in hypoid gears, hub reductions, gearboxes, PTO's and differentials where an API GL-5 , MIL-L 2105-D and Mack GO-G are recommended. The Eurol HPG 85W-90 can also be applied where MB 235.0 is prescribed.

Specifications

Performance level Voith 3.325-339
API GL-5 DAF
MIL-L-2105D
Recommended for use
MAN 342 Type M1
MB 235.0
ZF TE-ML
05C/07A/12B/16B/16C/16
D/16E/17B/19B/21A/21C
Volvo 97316
Volvo 97310

Physical properties

Colour	Brown	
Density at 20°C	0.897 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	194.4 cSt	ASTM D 445
Viscosity, kinematic at 100°C	17.6 cSt	ASTM D 445
Viscosity Index	98	ASTM D 2270
Flash point	250 °C	ASTM D 93
Pour point	-27 °C	ASTM D 97

Available in 1L - 5L - 20L - 25L - 60L - 200L - 210L - IBC